

EPT-55 Series

An excellent heavy-duty manual pallet truck for customers who want performance and value.

CAPACITY

- 5500 lb

OPERATION

- 200° handle pivot
- Only requires ten full strokes to reach maximum elevated height of 7.8"
- Control handle has three position (raise/neutral/lower) fingertip control
- Spring-loaded handle returns to upright position automatically
- Padded grip handle

HYDRAULICS

- Galvanized hydraulic pump includes an overload relief valve and lowering can be actuated by either hand or foot pedal release

FORKS / CHASSIS

- Climber rollers for easy entry into pallets
- Exit rollers mounted on hanger bracket reduces wear and allows for easy exiting of pallets
- Heavy-duty frame constructed of one-piece formed channel
- Adjustable push rods
- Durable cast iron hangers
- Easy maintenance—grease fitting and bushings at all pivot points
- Frame is powder coated

WARRANTY

- Two year structural warranty
- Two year hydraulic pump warranty



Comfort Grip and Easy Access Controls



Galvanized Pump



Entry / Exit Rollers

| | | | |
|-----------------------------|--------------------|-------------------------|--------------|
| Designation | Model | EPT-55 / 27 x 48 | |
| | Load Capacity | 5500 lb | |
| Chassis Dimensions | Pallet Forks | Lowered Height | 2.9" |
| | | Fork Length | 48" |
| | | Fork Width | 6.25" |
| | | Overall Fork Widths | 20.5" or 27" |
| | Raised Fork Height | 7.8" | |
| Approximate Shipping Weight | 165 lb | | |

| | | | |
|---------------------------|---------------------------------------|---------------------------|------------------------------|
| Wheels and Rollers | Steering Wheel | Polyurethane on Steel Hub | 7" dia. x 2" |
| | Load Rollers | Polyurethane | 2.9" dia. x 3.6" |
| Performance | Turning Radius | | 52.5" |
| | Strokes to attain maximum lift | | 10 full |
| | Steering pivot range (degrees) | | 200° |
| | Type of pump control - lift / release | | Hand / Hand and Foot Release |
| | Pallet entry assist type | | Roller |