



TOUGHNESS COMES IN YOUR SIZE.

Our new Bull Series was born to work as hard as you do. So whether you choose our standard Bull model with three seats or our Longhorn edition with two rows and six individual seats, you have a UTV sized to fit your needs. From the job site, to the field, to the trails, you'll find plenty of power, precise handling and comfort beyond compare. Both models feature our premium red and silver paint scheme, so regardless of the job you're tackling, you'll look good doing it.



FEATURES:

- 700-class, SOHC, 4-valve fuel-injected engine
- Electric power steering (EPS)
- Tru-Torq® CVT drive system delivers constant belt tension
- Downhill engine braking
- Dial-Lok® means easy drive selection
- Fully-independent long travel suspension
- Anti-sway bar reduces body roll
- Four-wheel, twin-piston, large-diameter hydraulic disc brakes
- Long wheelbase
- Dual-range (Hi/Lo) drive and reverse
- Lots of storage and cup holders
- Recessed middle seats for passenger comfort
- Tool-free air filter under seat
- Battery under center hood
- Digital instrument panel provides real-time information
- Tough rotomolded doors



BULL SERIES UTILITY TASK VEHICLES YU700G & YU700GMP SPECIFICATIONS



	BULL	LONGHORN
Model	YU700G	YU700GMP
Engine Type	686cc liquid-cooled SOHC 4-stroke; 4 valves	686cc liquid-cooled SOHC 4-stroke; 4 valves
Bore x Stroke	102.0 mm x 84.0 mm	102.0 mm x 84.0 mm
Compression Ratio	10.0:1	10.0:1
Electronic Fuel Injection (EFI)	YANMAR Fuel Injection (YFI)	YANMAR Fuel Injection (YFI)
Ignition	TCl: Transistor Controlled Ignition	TCl: Transistor Controlled Ignition
Starting System	Electric	Electric
Transmission	YANMAR Tru-Torq V-belt with all-wheel engine braking; L, H, N, R	YANMAR Tru-Torq V-belt with all-wheel engine braking; L, H, N, R
Drive Train	YANMAR Dial-Lok; 3-way locking differential; 2WD, 4WD, locked 4WD; shaft drive	YANMAR Dial-Lok; 3-way locking differential; 2WD, 4WD, locked 4WD; shaft drive
Suspension (Front)	Independent double wishbone; 8.1" travel	Independent double wishbone; 8.1" travel
Suspension (Rear)	Independent double wishbone with anti-sway bar; 8.1" travel	Independent double wishbone with anti-sway bar; 8.1" travel
Brakes (Front and Rear)	Dual hydraulic disc	Dual hydraulic disc
Tires (Front)	AT25 x 8-12	AT25 x 8-12
Tires (Rear)	AT25 x 10-12	AT25 x 10-12
L x W x H	122.1 in x 64 in x 75.8 in	153.5 in x 64 in x 76.6 in
Wheelbase	84.1 in	115.6 in
Turning Radius	177.2 in	244.1 in
Ground Clearance	11.8 in	11.4 in
Fuel Capacity	9.7 gal	9.7 gal
Wet Weight**	1,431 lb	1,695 lb
Bed Capacity	600 lb	600 lb
Towing Capacity	1,500 lb	1,500 lb

**Wet weight includes the vehicle with all standard equipment and all fluids, including oil, coolant (as applicable) and a full tank of fuel. It does not include the weight of options or accessories. Wet weight is useful in making real-world comparisons with other models.